

Nonmetallic Hose Assembly - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4720-01-191-8831
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.391 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.605 inches
Minimum Inside Bending Radius:
2.880 inches
Connection Style:
Swivel nut, inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:

Electrostatic discharge capability

## Thready Qty Per Inch (tpi):

16 1st end

## **Burst Test Pressure:**

14000.0 pounds per square inch

# Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

#### Maximum Operating Pressure:

3000.0 pounds per square inch

#### **Thread Size:**

0.750 inches 1st end

#### Seat Angle:

8.5 degrees 1st end

### **Outer Covering Environmental Protection:**

Fuel resistant and oil resistant and solvent resistant and vibration resistant

## **Inside Surface Condition:**

Smooth

## Measuring Method And Length:

12.750 inches working

# **Thread Series Designator:**

Unjs 1st end

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

