

View Online at <https://aerobasegroup.com/nsn/4720-01-191-8837>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.861 inches

Temperature Rating:

-54.0 degrees celsius single response and 135.0 degrees celsius single response

Outside Diameter:

1.530 inches

Minimum Inside Bending Radius:

9.625 inches

Connection Style:

Swivel nut, flareless 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

14 2nd end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.516 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

23.625 inches

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 00624 and 26512 have indicated their part number contained asbestos prior to 1984; they continue to manufacture the same part number without asbestos after 1984

Thread Series Designator:

Uns 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0