NSN 4720-01-192-3516



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-192-3516 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.423 inches **Minimum Inside Bending Radius:** 3.500 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fiber and outer layer molded plastic **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and hydraulic solution resistant **Inside Surface Condition:**

Smooth Measuring Method And Length: 96.000 inches Thread Series Designator: Unf 1st end

Shelf Life:

N/a

NSN 4720-01-192-3516

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0