

View Online at <https://aerobasegroup.com/nsn/4720-01-192-4419>

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Tempurature Rating:

-55.0 degrees fahrenheit and 300.0 degrees fahrenheit

Outside Diameter:

0.484 inches

Minimum Inside Bending Radius:

2.000 inches

First End Connection Type:

Threaded internal tube

First End Thread Class:

3b

First End Thread Direction:

Right-hand

First End Seat Angle In Deg:

37.0

First End Connection Design:

Straight

Hose Or Tubing Specification/std Data:

Mil-h-13444, type 3 specification

Connection Style:

Swivel nut flare 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting zinc 1st end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

6000.0 pounds per square inch

First End Swivel Action Capability:

Included

Maximum Operating Pressure:

1500.0 pounds per square inch

First End Thread Series Designator:

Unjf

Seat Angle:

37.0 degrees 1st end

First End Thread Size:

0.438 inches

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and ozone resistant and mildew resistant and vibration resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13444 spec.