## NSN 4720-01-192-5861



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-192-5861 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.656 inches **Minimum Inside Bending Radius:** 2.500 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 10000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyester cord and outer layer braided polyester cord **Maximum Operating Pressure:** 2500.0 pounds per square inch **Thread Size:** 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 5000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end **Inside Surface Condition:** 

Inside Surface Condition:
Smooth

Measuring Method And Length:
107.500 inches

Thread Series Designator:
Unf 2nd end

## NSN 4720-01-192-5861

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0