NSN 4720-01-192-8124

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-192-8124 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.620 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.930 inches **Minimum Inside Bending Radius:** 6.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 11000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 2750.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 5500.0 pounds per square inch **Outer Covering Environmental Protection:** Weatherproof **Inside Surface Condition:** Smooth **Measuring Method And Length:** 27.625 inches Media For Which Designed:

vicula i oi willcii besigned

Fuel/oil, hydrocarbon single response

NSN 4720-01-192-8124

Nonmetallic Hose Assembly - Page 2 of 2



Inread Series Designator:
Unf 1st end
Specification Or Standard:
10 size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0