## NSN 4720-01-192-9523

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-192-9523 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.312 inches **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 9.250 inches **Supplementary Features:** This item has been reviewed for asbestos material; the current approved sources; 96906 and 99193 have indicated their part number contained asbestos material prior to 1984; they continue to manufacture the same part number without asbestos material after 1984 **Thread Series Designator:** Unjf 1st end Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 4720-01-192-9523

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0