Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-192-9610

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Tempurature Rating:

-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

Outside Diameter:

1.250 inches

Minimum Inside Bending Radius:

5.000 inches

Exterior Color:

Blue

Hose Or Tubing Specification/std Data:

Sae j517, 100r4 size 12-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

1200.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided textile yarn err-100

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

1.062 inches 2nd end

Seat Angle:

37.0 degrees 2nd end



Hydrostatic Test Pressure: 600.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Vacuum In Torr: 28.0 Inside Surface Condition: Smooth Measuring Method And Length: 130.000 inches Second End Swivel Action Capability: Not included **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end **Specification Data:** Sae j517, 100r4 size 12-81343 national std/spec Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A542a0
