## NSN 4720-01-192-9611

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-192-9611 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.840 inches **Minimum Inside Bending Radius:** 3.500 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Perforated outer cover **Burst Test Pressure:** 10000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyester cord and 2nd layer braided polyester cord and outer layer molded polyurethane **Maximum Operating Pressure:** 2500.0 pounds per square inch **Thread Size:** 0.750 inches 2nd end Seat Angle: 37.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 

**Thread Series Designator:** 

53.000 inches

Unf 2nd end

## NSN 4720-01-192-9611

Nonmetallic Hose Assembly - Page 2 of 2



	<b>L</b> -	16		ife	_
3	ne	п	_	пе	Ξ

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0