## NSN 4720-01-192-9613

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-192-9613 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.380 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.660 inches **Minimum Inside Bending Radius:** 2.500 inches **Exterior Color:** Black **Connection Style:** Swivel nut with compression sleeve 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Perforated outer cover **Burst Test Pressure:** 10000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyester cord and 2nd layer braided polyester cord and outer layer molded polyurethane **Maximum Operating Pressure:** 2500.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Outer Covering Environmental Protection:** Fire retardant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 

**Thread Series Designator:** 

Unf 1st end

20.000 inches

## NSN 4720-01-192-9613

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0