NSN 4720-01-192-9617

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-192-9617

Cross Sectional Shape:						
Round						
Thread Class:						
3b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.620 inches						
Tempurature Rating:						
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response						
Outside Diameter:						
0.930 inches						
Minimum Inside Bending Radius:						
6.000 inches						
Connection Style:						
Swivel nut with compression sleeve 2nd end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Features Provided:						
Reusable end fittings						
Burst Test Pressure:						
11000.0 pounds per square inch						
Layer Composition And Location:						
1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic						
Maximum Operating Pressure:						
2750.0 pounds per square inch						
Thread Size:						
0.875 inches 2nd end						
Seat Angle:						
37.0 degrees 2nd end						
Hydrostatic Test Pressure:						
5500.0 pounds per square inch						
Flow Angle:						
90.0 degrees 2nd end						

Smooth

Measuring Method And Length:

Oil resistant and ozone resistant Inside Surface Condition:

Outer Covering Environmental Protection:

116.000 inches

NSN 4720-01-192-9617

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ned:

Hydraulic fluid, water base single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0