

View Online at <https://aerobasegroup.com/nsn/4720-01-192-9625>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.380 inches

Temperature Rating:

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.660 inches

Minimum Inside Bending Radius:

2.500 inches

Exterior Color:

Black

Connection Style:

Swivel nut with compression sleeve 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Perforated outer cover

Burst Test Pressure:

10000.0 pounds per square inch

Layer Composition And Location:

1st layer braided polyester cord and 2nd layer braided polyester cord and outer layer molded polyurethane

Maximum Operating Pressure:

2500.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

5000.0 pounds per square inch

Outer Covering Environmental Protection:

Fire retardant

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.000 inches

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0