NSN 4720-01-192-9627

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-192-9627 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.380 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.660 inches **Minimum Inside Bending Radius:** 2.500 inches **Exterior Color:** Black **Connection Style:** Swivel nut with compression sleeve 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Perforated outer cover **Burst Test Pressure:** 10000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyester cord and 2nd layer braided polyester cord and outer layer molded polyurethane **Maximum Operating Pressure:** 2500.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Outer Covering Environmental Protection:** Fire retardant **Inside Surface Condition:** Smooth **Measuring Method And Length:**

Thread Series Designator:

Unf 1st end

16.000 inches

NSN 4720-01-192-9627

Nonmetallic Hose Assembly - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0