Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-192-9628
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.620 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.930 inches
Minimum Inside Bending Radius:
6.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
11000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
2750.0 pounds per square inch
Thread Size:
0.875 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
5500.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Oil resistant and ozone resistant
Inside Surface Condition:
Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 20.000 inches working Media For Which Designed: Hydraulic fluid, water base single response **Thread Series Designator:** Unf 2nd end **Specification Or Standard:** 10 size Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0