NSN 4720-01-192-9631

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-192-9631

Cross Sectional Shape:					
Round					
Thread Class:					
3b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.250 inches					
Tempurature Rating:					
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response					
Outside Diameter:					
0.530 inches					
Minimum Inside Bending Radius:					
1.250 inches					
Exterior Color:					
Black					
Connection Style:					
Swivel nut flare 2nd end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Burst Test Pressure:					
11000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded polytetrafluoroethylene					
Maximum Operating Pressure:					
2750.0 pounds per square inch					
Thread Size:					
0.438 inches 1st end					
Seat Angle:					
37.0 degrees 2nd end					
Hydrostatic Test Pressure:					
5500.0 pounds per square inch					
Flow Angle:					
90.0 degrees 2nd end					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
22.000 inches excluding end fittings					
Thread Series Designator:					

Unf 2nd end

NSN 4720-01-192-9631

Nonmetallic Hose Assembly - Page 2 of 2



_	_			_	
С.		ficatio	^-	C+	
•	neci	ticatio	n cor	Stanc	ıarn:

4 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0