

View Online at <https://aerobasegroup.com/nsn/4720-01-192-9647>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 0.735 inches and 0.781 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

**Outside Diameter:**

Between 1.203 inches and 1.265 inches

**Minimum Inside Bending Radius:**

9.500 inches

**Hose Or Tubing Specification/std Data:**

Mil-h-24135 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**First End Fitting Specification/std Data:**

Sae j516, type a-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting cadmium 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Thready Qty Per Inch (tpi):**

12 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

9000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer spirally wrapped corrosion resistant steel fabric err-100

**Maximum Operating Pressure:**

2250.0 pounds per square inch

**Thread Size:**

1.062 inches 1st end

**External Protection Type And Location (non-core):**

spring guard, round stainless steel coil

**Seat Angle:**

37.0 degrees 1st end

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and mildew resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

42.000 inches

**Special Features:**

External protection type and location- spring guard, round stainless steel coil , inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-24135 spec.