## NSN 4720-01-193-7693

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-193-7693 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.438 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.734 inches **Minimum Inside Bending Radius:** 5.750 inches Angle Between Rigid Elbow Fittings In Deg: **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Elbow 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** 1st layer spiral interlocked corrosion resistant steel and 2nd layer spiral interlocked corrosion resistant steel and outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 8.625 inches **Thread Series Designator:** 

N/a

Unf 1st end Shelf Life:

## NSN 4720-01-193-7693

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0