Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-194-1893

Crease Castional Change	
Cross Sectional Shape: Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.406 inches	
Tempurature Rating:	
65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response	
Angle Between Rigid Elbow Fittings In Deg:	
315.0	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Elbow 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
8000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
1500.0 pounds per square inch	
Thread Size:	
0.750 inches 2nd end	
Seat Angle:	
37.0 degrees 2nd end	
Flow Angle:	
90.0 degrees 2nd end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
27.250 inches	
Supplementary Features:	
This item has been reviewed for asbestos material. The current approved source, 98441, has indicated their pa	rt number contained
asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984	4
Thread Series Designator:	
Unjf 1st end	
Shelf Life:	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A542a0