## NSN 4720-01-194-5159

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-194-5159

G G G G G G G G G G G G G G G
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
2.000 inches
Tempurature Rating:
450.0 degrees fahrenheit single response
Outside Diameter:
2.625 inches
Minimum Inside Bending Radius:
10.000 inches
Connection Style:
Plain optional end 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Internal support
Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
2.000 inches 1st end
Hydrostatic Test Pressure:
1250.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
300.000 inches excluding end fittings
Media For Which Designed:
Steam single response
Thread Series Designator:
Npt 1st end
Specification Data:
81349-mil-dtl-29210 government specification
Shelf Life:
<b>N</b> //

N/a

## NSN 4720-01-194-5159

Nonmetallic Hose Assembly - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A542a0