## NSN 4720-01-194-5161

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-194-5161

Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.500 inches
Tempurature Rating:
450.0 degrees fahrenheit single response
Outside Diameter:
2.062 inches
Connection Style:
Plain optional end 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal pipe 1st end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
2500.0 pounds per square inch
First End Swivel Action Capability:
Not included
1 6
Layer Composition And Location:
1st layer braided steel wire err-100
•
1st layer braided steel wire err-100
1st layer braided steel wire err-100  Maximum Operating Pressure:
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch  Thread Size:
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch  Thread Size: 1.500 inches 2nd end
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch  Thread Size: 1.500 inches 2nd end  Hydrostatic Test Pressure:
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch  Thread Size: 1.500 inches 2nd end  Hydrostatic Test Pressure: 1250.0 pounds per square inch
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch  Thread Size: 1.500 inches 2nd end  Hydrostatic Test Pressure: 1250.0 pounds per square inch  Inside Surface Condition:
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch  Thread Size: 1.500 inches 2nd end  Hydrostatic Test Pressure: 1250.0 pounds per square inch  Inside Surface Condition: Smooth
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch  Thread Size: 1.500 inches 2nd end  Hydrostatic Test Pressure: 1250.0 pounds per square inch Inside Surface Condition: Smooth  Measuring Method And Length:
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch  Thread Size: 1.500 inches 2nd end  Hydrostatic Test Pressure: 1250.0 pounds per square inch Inside Surface Condition: Smooth  Measuring Method And Length: 300.000 inches excluding end fittings
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch  Thread Size: 1.500 inches 2nd end  Hydrostatic Test Pressure: 1250.0 pounds per square inch Inside Surface Condition: Smooth  Measuring Method And Length: 300.000 inches excluding end fittings Second End Swivel Action Capability:
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch  Thread Size: 1.500 inches 2nd end  Hydrostatic Test Pressure: 1250.0 pounds per square inch Inside Surface Condition: Smooth  Measuring Method And Length: 300.000 inches excluding end fittings  Second End Swivel Action Capability: Not included
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch  Thread Size: 1.500 inches 2nd end  Hydrostatic Test Pressure: 1250.0 pounds per square inch Inside Surface Condition: Smooth  Measuring Method And Length: 300.000 inches excluding end fittings Second End Swivel Action Capability: Not included Special Features:
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch  Thread Size: 1.500 inches 2nd end  Hydrostatic Test Pressure: 1250.0 pounds per square inch Inside Surface Condition: Smooth  Measuring Method And Length: 300.000 inches excluding end fittings  Second End Swivel Action Capability: Not included  Special Features: Stainless steel liner, 1.250 id, 0.013 thk
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 1.500 inches 2nd end Hydrostatic Test Pressure: 1250.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 300.000 inches excluding end fittings Second End Swivel Action Capability: Not included Special Features: Stainless steel liner, 1.250 id, 0.013 thk Media For Which Designed:
1st layer braided steel wire err-100  Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 1.500 inches 2nd end Hydrostatic Test Pressure: 1250.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 300.000 inches excluding end fittings Second End Swivel Action Capability: Not included Special Features: Stainless steel liner, 1.250 id, 0.013 thk Media For Which Designed: Steam single response

## NSN 4720-01-194-5161

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

81349-mil-dtl-29210 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0