

View Online at <https://aerobasegroup.com/nsn/4720-01-194-6826>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.173 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.640 inches

Minimum Inside Bending Radius:

2.000 inches

Connection Style:

Swivel nut, inverted flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

8.5 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Waterproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

34.000 inches working

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 00624 have indicated their part number contained asbestos prior to 1984; they continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Unf 2nd end

Specification Data:

81349-mil-h-25579 government specification

Specification Or Standard:

1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0