NSN 4720-01-195-3845

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-195-3845

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.930 inches
Minimum Inside Bending Radius:
6.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
11000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
2750.0 pounds per square inch
Thread Size:
0.875 inches 2nd end
Seat Angle:
Seat Angle: 37.0 degrees 2nd end
-
37.0 degrees 2nd end
37.0 degrees 2nd end Hydrostatic Test Pressure:
37.0 degrees 2nd end Hydrostatic Test Pressure: 5500.0 pounds per square inch
37.0 degrees 2nd end Hydrostatic Test Pressure: 5500.0 pounds per square inch Flow Angle:

181.000 inches working

Measuring Method And Length:

NSN 4720-01-195-3845

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 2nd end
Specification Or Standard:
10 size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0