

View Online at <https://aerobasegroup.com/nsn/4720-01-198-0645>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.250 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

1.810 inches

**Minimum Inside Bending Radius:**

16.500 inches

**Connection Style:**

Double threaded section, boss fitting gasket with lockout sealing 1st end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Threaded external boss 1st end

**Burst Test Pressure:**

16000.0 pounds per square inch

**Layer Composition And Location:**

1st layer spirally wrapped corrosion resistant steel fabric and 2nd layer spirally wrapped corrosion resistant steel fabric and 3rd layer spirally wrapped corrosion resistant steel fabric and 4th layer spirally wrapped corrosion resistant steel fabric and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

4000.0 pounds per square inch

**Seat Angle:**

37.0 degrees 1st end

**Flow Angle:**

90.0 degrees 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

26.687 inches working

**Media For Which Designed:**

Hydraulic fluid single response

**Specification Data:**

Mil-h-24135/9 government specification

**Specification Or Standard:**

20 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-24135 spec.