

View Online at <https://aerobasegroup.com/nsn/4720-01-198-0647>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-100.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

1.125 inches

Minimum Inside Bending Radius:

7.375 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

1.312 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

72.562 inches excluding end fittings

Special Features:

Two hose assemblys connected by 90.0 degree elbow; material c/o copper alloy nipple; stainless steel sleeve; stainless steel socket; first leg lg. 40.062 in.; second leg lg. 32.500 in.

Thread Series Designator:

Un 1st end

Specification Or Standard:

16 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0