Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-198-0655

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.000 inches
Supplementary Features:
This item has been reviewed for asbestos material. The current approved source, 99193, has indicated their part number contained
asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984
Thread Series Designator:
Unjf 1st end
Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

## NSN 4720-01-198-0655

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

