NSN 4720-01-198-2669

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-198-2669

Cross Sectional Shape:
Round
Inside Diameter:
1.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
2.125 inches
Minimum Inside Bending Radius:
20.000 inches
Exterior Color:
Black
Connection Style:
Gasket seal / optional end 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal boss 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided textile yarn and 3rd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
3000.0 pounds per square inch
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and mildew resistant and oil resistant and ozone resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
56.000 inches working
Special Features:
C/o hose assemblys connected by 90.0 degree elbow, first leg lg. 28.000 in.; 2nd lg. 28.000 in.
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Specification Data:
81343-sae100r5 professional/industrial association standard

N/a

Shelf Life:

NSN 4720-01-198-2669

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0