Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-198-2669

Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Tempurature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

2.125 inches

Minimum Inside Bending Radius:

20.000 inches

Exterior Color:

Black

Connection Style:

Gasket seal / optional end 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Threaded internal boss 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and 2nd layer braided textile yarn and 3rd layer braided steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

3000.0 pounds per square inch

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Abrasion resistant and mildew resistant and oil resistant and ozone resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

56.000 inches working

Special Features:

C/o hose assemblys connected by 90.0 degree elbow, first leg lg. 28.000 in.; 2nd lg. 28.000 in.

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Specification Data:

81343-sae100r5 professional/industrial association standard

Shelf Life:

N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0