## NSN 4720-01-198-2670

**Cross Sectional Shape:** 

**Inside Diameter:** 1.500 inches

**Tempurature Rating:** 

**Outside Diameter:** 

**Minimum Inside Bending Radius:** 

Fuel/oil, hydrocarbon single response

2.125 inches

20.000 inches

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-198-2670

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Exterior Color:				
Black				
Connection Style:				
Gasket seal / optional end 1st end				
End Connection Design:				
Elbow 1st end				
End Fitting Component And Material:				
Complete fitting steel all ends				
Connection Type:				
Threaded internal boss 1st end				
Second End Relationship With First End:				
Identical				
Burst Test Pressure:				
12000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided textile yarn err-100				
Maximum Operating Pressure:				
3000.0 pounds per square inch				
Hydrostatic Test Pressure:				
6000.0 pounds per square inch				
Flow Angle:				
90.0 degrees 1st end				
Outer Covering Environmental Protection:				
Abrasion resistant and mildew resistant and oil resistant and ozone resistant and weatherproof				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
79.250 inches working				
Special Features:				
Two hose assembly connected by 90.0 degree elbow; first leg lg 45.500 in.; second leg lg. 33.750 in.				
Media For Which Designed:				

## NSN 4720-01-198-2670

Nonmetallic Hose Assembly - Page 2 of 2



Spec	cific	ation	Data:
------	-------	-------	-------

81343-sae100r5 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0