Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-198-2820

| Cross | Sectional | Shape: |
|-------|-----------|--------|
|       |           |        |

Round

Thread Class:

3b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.219 inches

#### **Tempurature Rating:**

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.625 inches

Minimum Inside Bending Radius:

3.000 inches

#### **Exterior Color:**

Black

#### **Connection Style:**

Swivel nut flare 1st end

## **End Connection Design:**

Straight 1st end

# Connection Type:

Threaded internal tube 1st end

# **Burst Test Pressure:**

16000.0 pounds per square inch

## Layer Composition And Location:

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

## Maximum Operating Pressure:

3000.0 pounds per square inch

## Thread Size:

0.438 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

## Hydrostatic Test Pressure:

8000.0 pounds per square inch

## Inside Surface Condition:

Smooth

## Measuring Method And Length:

64.000 inches

## Media For Which Designed:

Fuel/oil, hydrocarbon single response

# **Thread Series Designator:**

Unf 1st end

# NSN 4720-01-198-2820

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

