Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-198-8633

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.300 inches |
| Outside Diameter: |
| 0.625 inches |
| Minimum Inside Bending Radius: |
| 2.500 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 16 1st end |
| Burst Test Pressure: |
| 16000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.688 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 25.000 inches |
| Thread Series Designator: |
| Un 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 4720-01-198-8633

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

