## NSN 4720-01-199-6581

Air Duct Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-199-6581

Cross Sectional Shape: Round Wall Thickness: 0.060 inches Inside Diameter: 1.250 inches first end Minimum Inside Bending Radius: 1.250 inches Endlength: 1.500 inches both ends Connection Style: Round first end Connection Type: Preformed both ends Features Provided: Ozone resistant End Inside Diameter: 1.250 inches both ends Maximum Operating Pressure: 40.0 pounds per square inch Measuring Method And Length: 6.500 inches External Operating Pressure: 2.0 pounds per square inch Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cross Sectional Shape
Wall Thickness: 0.060 inches Inside Diameter: 1.250 inches first end Minimum Inside Bending Radius: 1.250 inches Endlength: 1.500 inches both ends Connection Style: Round first end Connection Type: Preformed both ends Features Provided: Ozone resistant End Inside Diameter: 1.250 inches both ends Maximum Operating Pressure: 40.0 pounds per square inch Measuring Method And Length: 6.500 inches External Operating Pressure: 2.0 pounds per square inch Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
O.060 inches Inside Diameter: 1.250 inches first end Minimum Inside Bending Radius: 1.250 inches Endlength: 1.500 inches both ends Connection Style: Round first end Connection Type: Preformed both ends Features Provided: Ozone resistant End Inside Diameter: 1.250 inches both ends Maximum Operating Pressure: 40.0 pounds per square inch Measuring Method And Length: 6.500 inches External Operating Pressure: 2.0 pounds per square inch Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Inside Diameter:  1.250 inches first end  Minimum Inside Bending Radius:  1.250 inches  Endlength:  1.500 inches both ends  Connection Style:  Round first end  Connection Type:  Preformed both ends  Features Provided:  Ozone resistant  End Inside Diameter:  1.250 inches both ends  Maximum Operating Pressure:  40.0 pounds per square inch  Measuring Method And Length:  6.500 inches  External Operating Pressure:  2.0 pounds per square inch  Material:  Steel reinforcing wire  Style Designator:  Helically wound continous wire supported  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
Minimum Inside Bending Radius:  1.250 inches Endlength:  1.500 inches both ends Connection Style: Round first end Connection Type: Preformed both ends Features Provided: Ozone resistant End Inside Diameter: 1.250 inches both ends Maximum Operating Pressure: 40.0 pounds per square inch Measuring Method And Length: 6.500 inches External Operating Pressure: 2.0 pounds per square inch Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Minimum Inside Bending Radius:  1.250 inches  Endlength:  1.500 inches both ends  Connection Style: Round first end  Connection Type: Preformed both ends  Features Provided: Ozone resistant  End Inside Diameter: 1.250 inches both ends  Maximum Operating Pressure: 40.0 pounds per square inch  Measuring Method And Length: 6.500 inches  External Operating Pressure: 2.0 pounds per square inch  Material: Steel reinforcing wire  Style Designator: Helically wound continous wire supported  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	
Endlength:  1.500 inches both ends  Connection Style: Round first end  Connection Type: Preformed both ends  Features Provided: Ozone resistant  End Inside Diameter: 1.250 inches both ends  Maximum Operating Pressure: 40.0 pounds per square inch  Measuring Method And Length: 6.500 inches  External Operating Pressure: 2.0 pounds per square inch  Material: Steel reinforcing wire  Style Designator: Helically wound continous wire supported  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	
Endlength:  1.500 inches both ends  Connection Style: Round first end  Connection Type: Preformed both ends  Features Provided: Ozone resistant  End Inside Diameter: 1.250 inches both ends  Maximum Operating Pressure: 40.0 pounds per square inch  Measuring Method And Length: 6.500 inches  External Operating Pressure: 2.0 pounds per square inch  Material: Steel reinforcing wire  Style Designator: Helically wound continous wire supported  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	•
1.500 inches both ends  Connection Style: Round first end  Connection Type: Preformed both ends  Features Provided: Ozone resistant  End Inside Diameter: 1.250 inches both ends  Maximum Operating Pressure: 40.0 pounds per square inch  Measuring Method And Length: 6.500 inches  External Operating Pressure: 2.0 pounds per square inch  Material: Steel reinforcing wire  Style Designator: Helically wound continous wire supported  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	1.250 inches
Connection Style: Round first end Connection Type: Preformed both ends Features Provided: Ozone resistant End Inside Diameter: 1.250 inches both ends Maximum Operating Pressure: 40.0 pounds per square inch Measuring Method And Length: 6.500 inches External Operating Pressure: 2.0 pounds per square inch Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Endlength:
Round first end  Connection Type: Preformed both ends  Features Provided: Ozone resistant  End Inside Diameter: 1.250 inches both ends  Maximum Operating Pressure: 40.0 pounds per square inch  Measuring Method And Length: 6.500 inches  External Operating Pressure: 2.0 pounds per square inch  Material: Steel reinforcing wire  Style Designator: Helically wound continous wire supported  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	1.500 inches both ends
Connection Type: Preformed both ends Features Provided: Ozone resistant End Inside Diameter: 1.250 inches both ends Maximum Operating Pressure: 40.0 pounds per square inch Measuring Method And Length: 6.500 inches External Operating Pressure: 2.0 pounds per square inch Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Connection Style:
Preformed both ends  Features Provided: Ozone resistant  End Inside Diameter: 1.250 inches both ends  Maximum Operating Pressure: 40.0 pounds per square inch  Measuring Method And Length: 6.500 inches  External Operating Pressure: 2.0 pounds per square inch  Material: Steel reinforcing wire  Style Designator: Helically wound continous wire supported  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Round first end
Features Provided: Ozone resistant End Inside Diameter: 1.250 inches both ends Maximum Operating Pressure: 40.0 pounds per square inch Measuring Method And Length: 6.500 inches External Operating Pressure: 2.0 pounds per square inch Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Connection Type:
Ozone resistant  End Inside Diameter:  1.250 inches both ends  Maximum Operating Pressure:  40.0 pounds per square inch  Measuring Method And Length: 6.500 inches  External Operating Pressure: 2.0 pounds per square inch  Material: Steel reinforcing wire  Style Designator: Helically wound continous wire supported  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Preformed both ends
End Inside Diameter:  1.250 inches both ends  Maximum Operating Pressure:  40.0 pounds per square inch  Measuring Method And Length:  6.500 inches  External Operating Pressure:  2.0 pounds per square inch  Material:  Steel reinforcing wire  Style Designator:  Helically wound continous wire supported  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Features Provided:
1.250 inches both ends  Maximum Operating Pressure:  40.0 pounds per square inch  Measuring Method And Length:  6.500 inches  External Operating Pressure:  2.0 pounds per square inch  Material:  Steel reinforcing wire  Style Designator:  Helically wound continous wire supported  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Ozone resistant
Maximum Operating Pressure:  40.0 pounds per square inch  Measuring Method And Length: 6.500 inches  External Operating Pressure: 2.0 pounds per square inch  Material: Steel reinforcing wire  Style Designator: Helically wound continous wire supported  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	End Inside Diameter:
40.0 pounds per square inch  Measuring Method And Length: 6.500 inches  External Operating Pressure: 2.0 pounds per square inch  Material: Steel reinforcing wire  Style Designator: Helically wound continous wire supported  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.250 inches both ends
Measuring Method And Length:  6.500 inches  External Operating Pressure:  2.0 pounds per square inch  Material:  Steel reinforcing wire  Style Designator:  Helically wound continous wire supported  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Maximum Operating Pressure:
6.500 inches  External Operating Pressure: 2.0 pounds per square inch  Material: Steel reinforcing wire  Style Designator: Helically wound continous wire supported  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	40.0 pounds per square inch
External Operating Pressure:  2.0 pounds per square inch  Material: Steel reinforcing wire  Style Designator: Helically wound continous wire supported  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Measuring Method And Length:
2.0 pounds per square inch  Material: Steel reinforcing wire  Style Designator: Helically wound continous wire supported  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	6.500 inches
Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	External Operating Pressure:
Steel reinforcing wire  Style Designator:  Helically wound continous wire supported  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	2.0 pounds per square inch
Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Helically wound continous wire supported  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel reinforcing wire
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Helically wound continous wire supported
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
-	Fiig:
A229a0	A229a0