
Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-200-2803

Cross Sectional S	hape:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.410 inches	
Outside Diameter	
0.700 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut, flareles	s 1st end
End Connection E	esign:
Straight 1st end	
Connection Type:	
Threaded internal t	ube 1st end
Burst Test Pressu	re:
900.0 pounds per s	quare inch
Layer Compositio	n And Location:
1st layer braided co	prrosion resistant steel wire and 2nd layer braided textile yarn and outer layer braided polyester cord
Maximum Operati	ng Pressure:
225.0 pounds per s	quare inch
Thread Size:	
0.750 inches 1st er	ıd
Seat Angle:	
12.0 degrees 1st e	nd
Hydrostatic Test I	Pressure:
450.0 pounds per s	quare inch
Outer Covering E	nvironmental Protection:
Fire retardant	
Inside Surface Co	ndition:
Smooth	
Measuring Metho	And Length:
30.500 inches wor	king and 31.500 inches working
Thread Series Des	signator:
Unjf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 4720-01-200-2803

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

