Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-202-9561

Round

**Thread Class:** 

3b 1st end

## **Thread Direction:**

Right-hand 1st end

## Inside Diameter:

0.391 inches

#### **Tempurature Rating:**

-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.605 inches

Minimum Inside Bending Radius:

2.880 inches

#### Connection Style:

Swivel nut flare 1st end

# End Connection Design:

Straight 1st end

## **Connection Type:**

Threaded internal tube 1st end

# Features Provided:

Electrostatic discharge capability and reusable end fittings

### **Burst Test Pressure:**

10500.0 pounds per square inch

### Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

### Maximum Operating Pressure:

3000.0 pounds per square inch

#### **Thread Size:**

0.562 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

### Hydrostatic Test Pressure:

6000.0 pounds per square inch

### **Outer Covering Environmental Protection:**

Fuel resistant and oil resistant and solvent resistant and heat resistant

# Inside Surface Condition:

Smooth

### Measuring Method And Length:

28.500 inches

## **Thread Series Designator:**

Unjf 1st end

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

