NSN 4720-01-205-1098

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-205-1098

3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 160.0 degrees fahrenheit single response
Outside Diameter:
1.200 inches
Minimum Inside Bending Radius:
3.500 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Fitting Component And Surface Treatment:
Complete fitting zinc 1st end
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
900.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer polyester err-100
Maximum Operating Pressure:
225.0 pounds per square inch
Thread Size:
1.312 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
450.0 pounds per square inch

NSN 4720-01-205-1098

Nonmetallic Hose Assembly - Page 2 of 2



Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
56.000 inches
Second End Swivel Action Capability:
Not included
Special Features:
Inner conveying tube material-silicone rubber
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0