## NSN 4720-01-205-5187

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-205-5187

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.292 inches and 0.332 inches
Tempurature Rating:
-50.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
Between 0.485 inches and 0.525 inches
Minimum Inside Bending Radius:
5.500 inches
Connection Style:
Inverted flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
400.0 pounds per square inch
Layer Composition And Location:
2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided corrosion resistant steel wire
Maximum Operating Pressure:
100.0 pounds per square inch
Thread Size:
0.5625 inches 1st end
Seat Angle:
90.0 degrees 2nd end
Hydrostatic Test Pressure:
200.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
39.500 inches working and 41.500 inches working
Seat Radius:
0.015 inches 1st end
Thread Series Designator:

Unjf 1st end

## NSN 4720-01-205-5187

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

53711-5187925 manufacturers source control

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0