Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-206-6060

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.391 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response	
Outside Diameter:	
0.585 inches	
Minimum Inside Bending Radius:	
4.620 inches	
Connection Style:	
Swivel nut, flareless 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
8000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
15000.0 pounds per square inch	
Thread Size:	
0.750 inches 2nd end	
Seat Angle:	
12.0 degrees 2nd end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
Flow Angle:	
90.0 degrees 2nd end	
Vacuum In Torr:	
50.8	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
12.375 inches working	
Thread Series Designator:	
Unjf 1st end	

NSN 4720-01-206-6060

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

