NSN 4720-01-207-1071

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-207-1071

Cross Sectional Shape:						
Round						
Thread Class:						
3b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.375 inches						
Tempurature Rating:						
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response						
Outside Diameter:						
0.680 inches						
Minimum Inside Bending Radius:						
3.500 inches						
Exterior Color:						
Black						
Connection Style:						
Swivel nut flare 2nd end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Features Provided:						
Reusable end fittings						
Burst Test Pressure:						
16000.0 pounds per square inch						
Layer Composition And Location:						
1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic						
Maximum Operating Pressure:						
4000.0 pounds per square inch						
Thread Size:						
0.562 inches 2nd end						
Seat Angle:						
37.0 degrees 2nd end						
Hydrostatic Test Pressure:						
8000.0 pounds per square inch						
Flow Angle:						
90.0 degrees 2nd end						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						

18.000 inches working

NSN 4720-01-207-1071

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ed

Hydraulic fluid single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0