Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-207-1074

Cross	Sectional	Shape:
-------	-----------	--------

Round

**Thread Class:** 

3b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.375 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.680 inches

Minimum Inside Bending Radius:

#### 3.500 inches

**Exterior Color:** 

Black

#### **Connection Style:**

Swivel nut flare 2nd end

#### **End Connection Design:**

Straight 1st end

## Connection Type:

Threaded internal tube 1st end

### **Features Provided:**

Reusable end fittings

#### **Burst Test Pressure:**

16000.0 pounds per square inch

#### Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

#### Maximum Operating Pressure:

4000.0 pounds per square inch

#### Thread Size:

0.562 inches 2nd end

#### Seat Angle:

37.0 degrees 2nd end

#### Hydrostatic Test Pressure:

8000.0 pounds per square inch

### Flow Angle:

90.0 degrees 2nd end

# Inside Surface Condition:

Smooth

### Measuring Method And Length:

120.000 inches working



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Specification Or Standard:

6 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0