Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-207-1076

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

### **Outside Diameter:**

0.680 inches

Minimum Inside Bending Radius:

#### 3.500 inches

**Exterior Color:** 

Black

## **Connection Style:**

Swivel nut flare 2nd end

## **End Connection Design:**

Straight 1st end

# Connection Type:

Threaded internal tube 1st end

## **Features Provided:**

Reusable end fittings

## **Burst Test Pressure:**

16000.0 pounds per square inch

#### Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

### Maximum Operating Pressure:

4000.0 pounds per square inch

#### Thread Size:

0.562 inches 2nd end

#### Seat Angle:

37.0 degrees 2nd end

#### Hydrostatic Test Pressure:

8000.0 pounds per square inch

## Flow Angle:

90.0 degrees 2nd end

# Inside Surface Condition:

Smooth

## Measuring Method And Length:

48.000 inches working



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Specification Or Standard:

6 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0