NSN 4720-01-207-1094

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-207-1094

Cross Sectional Shape:				
Round				
Thread Class:				
2b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.375 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response				
Outside Diameter:				
0.688 inches				
Minimum Inside Bending Radius:				
5.000 inches				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
9000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided steel wire and outer layer molded rubber, chloroprene				
Maximum Operating Pressure:				
2250.0 pounds per square inch				
Thread Size:				
0.562 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
4500.0 pounds per square inch				
Outer Covering Environmental Protection:				
Abrasion resistant and oil resistant and weatherproof				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
160.000 inches				
Thread Series Designator:				
Unf 1st end				
Shelf Life:				
N/a				

N/a

NSN 4720-01-207-1094

Nonmetallic Hose Assembly - Page 2 of 2



ι	Jn	it	Of	Measure:	•

--

Demilitarization:

No

Fiig:

A542a0