NSN 4720-01-207-1095

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-207-1095 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.688 inches **Minimum Inside Bending Radius:** 5.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 2250.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 4500.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and ozone resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:**

50.000 inches **Thread Series Designator:** Unf 1st end Shelf Life: N/a

NSN 4720-01-207-1095

Nonmetallic Hose Assembly - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0