Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-207-1098

Cross Sectional	Shane.
Round	
Thread Class:	
2b 1st end	
Thread Direction	
Right-hand 1st en	
Inside Diameter:	
0.500 inches	
Tempurature Ra	ting:
	renheit and 250.0 degrees fahrenheit single response
Outside Diamete	
0.875 inches	
	Bending Radius:
7.000 inches	
Connection Style	
Swivel nut flare 1	
End Connection	
Straight 1st end	
Connection Type	2:
Threaded internal	
Features Provide	ed:
Nonskive	
Burst Test Press	sure:
14000.0 pounds p	per square inch
Layer Compositi	on And Location:
1st layer braided	corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber,
chloroprene	
Maximum Opera	ting Pressure:
3500.0 pounds pe	er square inch
Thread Size:	
0.875 inches 1st	end
Seat Angle:	
37.0 degrees 1st	end
Outer Covering	Environmental Protection:
Abrasion resistan	t and oil resistant and weatherproof
Inside Surface C	ondition:
Smooth	
Measuring Methe	od And Length:
94.000 inches	
Thread Series De	esignator:
Unf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0