NSN 4720-01-208-2051

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-208-2051

One of Continued Observer
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
0.766 inches
Minimum Inside Bending Radius:
4.625 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Weatherproof and corrosion resistant and fuel resistant and water resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
60.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response

Unjf 1st end

Thread Series Designator:

NSN 4720-01-208-2051

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0