NSN 4720-01-208-2052

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-208-2052

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
1.234 inches
Minimum Inside Bending Radius:
7.375 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
3200.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
800.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Alcohol resistant and corrosion resistant and fuel resistant and water resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
288.000 inches

Fuel/oil, hydrocarbon single response

Media For Which Designed:

NSN 4720-01-208-2052

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:
--------	--------	-------------

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0