## NSN 4720-01-208-4818

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-208-4818

| Cross Sectional Shape:  |
|---|
| Round   |
| Inside Diameter:  |
| 0.380 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.680 inches  |
| Minimum Inside Bending Radius:  |
| 3.500 inches  |
| End Application:  |
| Jlg industries crane model 8812   |
| Burst Test Pressure:  |
| 16000.0 pounds per square inch  |
| Layer Composition And Location:   |
| 1st layer braided steel wire and outer layer molded rubber, synthetic                 |
| Maximum Operating Pressure:   |
| 4000.0 pounds per square inch   |
| Hydrostatic Test Pressure:  |
| 8000.0 pounds per square inch   |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 42.000 inches working   |
| Media For Which Designed:   |
| Fuel/oil, hydrocarbon single response   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <u></u>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A542a0  |
|   |
|   |
|   |