## NSN 4720-01-209-6502



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-209-6502 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** Between 0.173 inches and 0.203 inches **Outside Diameter:** Between 0.304 inches and 0.343 inches **Minimum Inside Bending Radius:** 2.000 inches **Connection Style:** Swivel nut, gasket seal 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal hose 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and outer layer braided steel wire **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.500 inches 1st end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 2.100 inches working **Thread Series Designator:** Unef 1st end **Specification Data:** 96906-ms8001 government standard Shelf Life: N/a

**Demilitarization:** No

**Unit Of Measure:** 

## NSN 4720-01-209-6502

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0