## NSN 4720-01-210-1308

Air Duct Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-210-1308

| Cross Sectional Shape:  |
|---|
| Round   |
| Inside Diameter:  |
| 0.750 inches first end  |
|   |
| Minimum Inside Bending Radius: 0.375 inches   |
|   |
| Endlength:  |
| 1.550 inches first end  |
| Connection Style:   |
| Round first end   |
| Connection Type:  |
| Soft first end  |
| Features Provided:  |
| Stowage device  |
| End Inside Diameter:  |
| 0.750 inches first end  |
| Maximum Operating Pressure:   |
| 16.0 pounds per square inch   |
| Measuring Method And Length:  |
| 10.000 inches   |
| Material Specification:   |
| Qq-w-423, form 1, comp 302, cond 3 federal specification single material response 2nd ply |
| Style Designator:   |
| Helically wound continous wire supported  |
| Specification Data:   |
| 81349-mil-h-8796 government specification   |
| Specification Or Standard:  |
| 2 type and 2 class  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A229a0  |
| Mil-std (military Standard):  |
| Mil-h-8796 spec.  |
| <del></del>   |