NSN 4720-01-211-1995

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-211-1995 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** Between 0.851 inches and 0.906 inches **Outside Diameter:** Between 1.078 inches and 1.140 inches **Minimum Inside Bending Radius:** 7.375 inches **Connection Style:** Swivel nut, gasket seal 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal hose 2nd end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and outer layer braided steel wire **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 1.375 inches 2nd end **Hydrostatic Test Pressure:** 2500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 4.000 inches working **Thread Series Designator:** Unef 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 4720-01-211-1995

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0