NSN 4720-01-211-4508

Thread Series Designator:

Unf 2nd end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-211-4508

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.229 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response
Outside Diameter:
0.495 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Natural Natural
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
25500.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer spirally laid corrosion resistant steel wire and 3rd layer spirally laid corrosion
resistant steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
6000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
12000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
72.000 inches

NSN 4720-01-211-4508

Nonmetallic Hose Assembly - Page 2 of 2



She	lf I	Life	е:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0