NSN 4720-01-212-0277

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-212-0277
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.125 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
0.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:

Outer Covering Environmental Protection:

Abrasion resistant and weatherproof and fuel resistant and oil resistant and water resistant

Inside Surface Condition:

600.0 pounds per square inch

Smooth

Measuring Method And Length:

60.000 inches working

NSN 4720-01-212-0277

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:	
Air single response	
Thread Series Designator:	
Unf 1st end	
Specification Data:	
88044-an6270 government standard	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A542a0